



3M 051115-16510 Moldable Fire Barrier Putty Stix, 6.1 cu-in, Red

Details

Locke Part #: **P0166**
Mfg. Part #: **MPP 9.5"x9.5"**
Manufacturer: **3M**

Features

9.5 in length
9.5 in width
Firestop tested up-to 4 hr in accordance with ASTM E 814 (UL 1479) and CAN/ULC-S115
Wall opening protective tested up-to 2 hr in accordance with UL 263
Provides draft and cold smoke seal
Pliable and conformable molds easily into required shape
Helps reduce noise transfer
Excellent adhesion
Re-enterable/repairable
Halogen free and solvent free
Excellent aging properties
Low-VOC
Will not dry out or crumble
Red color widely recognized as a fire protective product
1/10 in thickness
10 to 12 lb/gal nominal density
Flame spread 0, smoke development 0 surface burning
Begins at 350 deg F/significant at 400 deg F heat expansion
1/8 in pad size

Attributes

Color: **Red**
Container Size: **6.1 cu-in**
Country of Origin: **USA**
Drying Time: **4**
Mfg Standards/Approvals: **cUL Listed, FM Approved, UL Listed**
Net Weight: **7.6**
Package Height: **2.75**
Package Length: **11.875**
Package Weight: **13.3**
Package Width: **10.25**
Type: **Moldable**
VOC Content: **250 g/L**

Resources

[Brochure](#)
[Material Safety Sheet](#)
[Specification Sheet](#)
[Specification Sheet](#)
[Technical Drawing](#)

[View Item Online](#)

Printed on: 11/15/2018