



DELTA Monitor 14 Victorian Tub Trim, 2.5 gpm, Venetian Bronze, Non-Diverter Spout, Commercial

Details

Locke Part #: **A1928**
Mfg. Part #: **T14155-RBLHP**
Manufacturer: **DELTA**


Features

Monitor Scald-Guard valve keeps water temperature within +/-3 deg F
Includes 7-1/2 in long non-diverter tub spout
Monitor 14 series pressure balanced bath mixing valve trim
Maintains a balanced pressure of hot and cold water even when a valve is turned on or off elsewhere in the system
Back-to-back installation capability
Temperature only controlled with handle
Field Adjustable to limit handle rotation into hot water zone
120 deg maximum handle rotation
All parts replaceable from the front of the valve
RP77991 adds 1 3/4 in to max installation thickness
Hot cold indicator
Sweat onto 1/2 in CWT or thread onto 1/2 in IPS
2.5 gpm at 80 psi

Attributes

Collection: **Victorian**
Commercial/Residential: **Commercial**
Connection Size: **1/2 in**
Connection Type: **IPS**
Finish/Color: **Venetian Bronze**
Flow Rate: **2.5 gpm**
Material: **Brass**
Mfg Standards/Approvals: **ASME A112.18.1, ASSE 1016, CSA B125.1**
Mounting Type: **Wall**
Number of Faucet Holes: **4**
Package Height: **4.625**
Package Length: **25.5**
Package Volume: **0.61**
Package Weight: **1.7694**
Package Width: **9**
Series: **Monitor 14**
Spout Reach: **7-1/2 in**
Spout Type: **Non-Diverter**
Valve/Cartridge Type: **Pressure Balanced Valve**

Resources

-  [Data/Spec Sheet](#)
-  [Instruction/Installation Sheet](#)

[View Item Online](#)