



## DELTA R2707 Roman Tub Rough, 18 gpm, 8 to 16 in

### Details

Locke Part #: **A2028**  
Mfg. Part #: **R2707**  
Manufacturer: **DELTA**

### Features

Roman tub rough-in installation kit  
Self-locating basis  
Tighten/adjust from above the deck  
5/8 in O.D. copper supply inlet tubes  
5/8 in O.D. corrugated copper supply outlet tubes  
Widespread 16 in (406 mm) maximum centers without using additional tubing  
Flexible deck or ledge mount installation  
Solid fabricated brass end valves and spout body  
Control mechanism shall be of the rotating cylinder type with ceramic plate and 180 deg rotation, with replaceable ceramic seats operating in stainless steel lined sockets  
Hot and cold stems are interchangeable  
Temperature and volume controlled with handles  
All operating parts shall be replaceable from the top  
18 gpm at 60 psi

### Attributes

Center Distance: **8 to 16 in**  
Flow Rate: **18 gpm**  
Material: **Brass**  
Maximum Deck Thickness: **2-1/4 in**  
Mfg Standards/Approvals: **ASME A112.18.1, CSA B125.1**  
Number of Faucet Holes: **3**  
Pack Quantity: **3**  
Package Height: **16.25**  
Package Length: **9**  
Package Volume: **0.614**  
Package Weight: **3.2476**  
Package Width: **7.25**  
Valve/Cartridge Type: **Washerless Stem**

### Resources

- Data/Spec Sheet
- Instruction/Installation Sheet
- Parts List

[View Item Online](#)

Printed on: 2/16/2019